

ASSO 75 Open

CANOTTI PNEUMATICI

Technical characteristics

Overall length cm. 750

Inside length cm. 300

Tubes diameter cm. 59 – n. 6 compartments

Dimensions with deflated tubes cm. 700 x 250

Weight Kg. 730 approx without engine

Engine power max Kw 224 - HP 304 – XL

Outboard engine max weight Kg. 400

Maximum load n. 20 people– Kg. 1800

CE Category “B” Type - VIII

Standard equipment

Standard tube/strips colors: Neptune Gray/red

Rubber fenders

Repair kit + manual inflation pump + n. 2 paddles

Grp bow platform with anchor roller

N° 4 mooring cleat

N° 6 Stainless steel tow and lift rings

Stern platform with stainless steel ladder

N°6 Lockers

Stainless steel rails system on the deck

Neoprene/hypalon 1670 dtex fabric

Electric inflation pump

Optionals

Battery with 12V DC power system

Compass

Waterproof cover for console

Storage cover

Custom colors tubes

Driving console model: E/ E2/F/A-75/ Rescue

Lifting sling kit

Grp locker Top line model

Electric control panel

Electric inflation pump

Electric bilge pump

Gasoline tank with complete fuel fittings

Socket for cigarette-lighter (12 Volt)

Radio VHF with aerial

Stainless steel arch with navigation lights

Flashing light blue/orange/yellow

Folding sun tent to roll bar

Diving bottles holder

Additional fuel tank

Electric horn

Pilot seat stand-up (easy or top line model)

Semi-Automatic anti-capsized stainless steel arch

Fresh water system

Side door opening

Electric windlass



Specifications and components listed are subject to change by the manufacturer without notice.