

ASSO 50

CANOTTI PNEUMATICI

Technical characteristics

Overall length cm. 506
Beam cm. 229
Tubes diameter cm. 55 – n. 5 compartments
Dimensions when the boat is deflated cm. 442 x 150
Weight Kg. 320 approx without engine
Engine power Kw 73,3 - HP 100 – Long shaft
Outboard engine max weight Kg. 150
Maximum load n. 8 people – max Kg. 720
CE Category - Type "C" Type VII
Self draining Rib

Standard equipment

Standard tube/strips colors: Pearl/Blue or Pearl/Amaranth
Driving console with windshield, hatches, wheel and handrail
Double rubber fenders
Bow locker for ropes and anchor
Repair kit + manual air pump + n. 2 paddles
Grp bow platform and stainless steel anchor roller
n. 1 bow mooring cleat
n. 6 lockers
Stern platform with stainless steel ladder
N° 3 Stainless steel for tow and lift rings
Driving seat foldable

Optionals

Battery with 12 V DC power system, Compass
Waterproof cover for console, Storage cover
Custom colors tubes, Bow sun-deck upholstery
Lifting sling kit, Fresh water system
Electric control panel
Electric inflation pump
Electric bilge pump
Manual bilge pump
Socket for cigarette-lighter (12 Volt)
Radio VHF with aerial
Stainless steel arch with navigation lights
Gasoline tank with complete fuel fittings
Folding sun tent to roll bar
Telescopic folding sun tent to roll bar
Neoprene/hypalon Fabric 1670 DTEX
Electric horn

Accessories included in the EXL version

Waterproof cover for console
Bow sun-deck upholstery
Electric control panel
Electric bilge pump
Gasoline tank with complete fuel fittings



Specifications and components listed are subject to change by the manufacturer without notice.